

Package: leaflet.extras (via r-universe)

September 2, 2024

Type Package

Title Extra Functionality for 'leaflet' Package

Version 2.0.1.9000

Description The 'leaflet' JavaScript library provides many plugins some of which are available in the core 'leaflet' package, but there are many more. It is not possible to support them all in the core 'leaflet' package. This package serves as an add-on to the 'leaflet' package by providing extra functionality via 'leaflet' plugins.

License GPL-3 | file LICENSE

Encoding UTF-8

Depends R (>= 3.1.0), leaflet (>= 2.0.0)

Imports htmlwidgets, htmltools, stringr, magrittr

Suggests jsonlite, readr, sf, xfun, testthat (>= 3.0.0)

URL <https://github.com/trafficonese/leaflet.extras>,
<https://trafficonese.github.io/leaflet.extras/>

BugReports <https://github.com/trafficonese/leaflet.extras/issues>

RoxygenNote 7.3.1

Config/testthat.edition 3

Repository <https://trafficonese.r-universe.dev>

RemoteUrl <https://github.com/trafficonese/leaflet.extras>

RemoteRef HEAD

RemoteSha 91b6fb07c383b286cd665b0a654ccc5c5242660a

Contents

addAwesomeMarkersDependencies	2
addBingTiles	3
addBootstrapDependency	4

addBounceMarkers	4
addDrawToolbar	6
addFullscreenControl	8
addGeoJSONv2	9
addGroupedLayersControl	18
addGroupedOverlay	19
addHash	20
addHeatmap	20
addResetMapButton	24
addSearchFeatures	24
addSearchOSM	25
addStyleEditor	27
addWebGLHeatmap	28
addWMSLegend	33
debugMap	34
drawShapeOptions	34
edithandlersOptions	38
edittoolbarOptions	38
enableMeasurePath	39
enableTileCaching	40
geodesics	41
gpsOptions	44
groupedLayersControlOptions	45
handlersOptions	46
leafletExtrasDependencies	47
propsToHTML	48
pulseIconList	49
searchOptions	51
suspendScroll	53
toolbarOptions	54
weatherIconList	55

Index	58
--------------	-----------

addAwesomeMarkersDependencies

Add AwesomeMarkers and related lib dependencies to a map

Description

Add AwesomeMarkers and related lib dependencies to a map

Usage

`addAwesomeMarkersDependencies(map, libs)`

Arguments

map	the map widget
libs	char vector with lib names.

addBingTiles	<i>Adds Bing Tiles Layer</i>
--------------	------------------------------

Description

Adds Bing Tiles Layer

Usage

```
addBingTiles(  
    map,  
    apikey = Sys.getenv("BING_MAPS_API_KEY"),  
    imagerySet = c("Aerial", "AerialWithLabels", "AerialWithLabelsOnDemand",  
        "AerialWithLabelsOnDemand", "Birdseye", "BirdseyeWithLabels", "BirdseyeV2",  
        "BirdseyeV2WithLabels", "CanvasDark", "CanvasLight", "CanvasGray", "Road",  
        "RoadOnDemand", "Streetside"),  
    layerId = NULL,  
    group = NULL,  
    ...  
)
```

Arguments

map	The Map widget
apikey	String. Bing API Key
imagerySet	String. Type of Tiles to display
layerId	String. An optional unique ID for the layer
group	String. An optional group name for the layer
...	Optional Parameters required by the Bing API described at https://learn.microsoft.com/en-us/bingmaps/getting-started/bing-maps-dev-center-help/getting-a-bing-maps-key?redirectedfrom=MSDN

See Also

Get a Bing Maps API Key: <https://learn.microsoft.com/en-us/bingmaps/rest-services/imagery/get-imagery-metadata?redirectedfrom=MSDN>

addBootstrapDependency

Add Bootstrap dependency to a map

Description

Add Bootstrap dependency to a map

Usage

addBootstrapDependency(map)

Arguments

map the map widget

addBounceMarkers

Add Bounce Markers to map

Description

Add Bounce Markers to map

Usage

```
addBounceMarkers(  
    map,  
    lng = NULL,  
    lat = NULL,  
    layerId = NULL,  
    group = NULL,  
    icon = NULL,  
    duration = 1000,  
    height = 100,  
    popup = NULL,  
    popupOptions = NULL,  
    label = NULL,  
    labelOptions = NULL,  
    options = leaflet::markerOptions(),  
    data = leaflet::getMapData(map)  
)
```

Arguments

map	a map widget object created from leaflet()
lng	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
icon	the icon(s) for markers; an icon is represented by an R list of the form <code>list(iconUrl = "?", iconSize = c(x, y))</code> , and you can use icons() to create multiple icons; note when you use an R list that contains images as local files, these local image files will be base64 encoded into the HTML page so the icon images will still be available even when you publish the map elsewhere
duration	integer scalar: The duration of the animation in milliseconds.
height	integer scalar: Height at which the marker is dropped.
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using htmlEscape() for security reasons)
popupOptions	A Vector of popupOptions to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of labelOptions to provide label options for each label. Default NULL
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
data	the data object from which the argument values are derived; by default, it is the <code>data</code> object provided to <code>leaflet()</code> initially, but can be overridden

Author(s)

Markus Dumke

See Also

[GitHub: leaflet.bouncemarker](#)

Examples

```
leaflet() %>%
  addTiles() %>%
  addBounceMarkers(49, 11)
```

addDrawToolbar	<i>Adds a Toolbar to draw shapes/points on the map.</i>
----------------	---

Description

Adds a Toolbar to draw shapes/points on the map.

Removes the draw toolbar

Usage

```
addDrawToolbar(
  map,
  targetLayerId = NULL,
  targetGroup = NULL,
  position = c("topleft", "topright", "bottomleft", "bottomright"),
  polylineOptions = drawPolylineOptions(),
  polygonOptions = drawPolygonOptions(),
  circleOptions = drawCircleOptions(),
  rectangleOptions = drawRectangleOptions(),
  markerOptions = drawMarkerOptions(),
  circleMarkerOptions = drawCircleMarkerOptions(),
  editOptions = FALSE,
  singleFeature = FALSE,
  toolbar = NULL,
  handlers = NULL,
  edittoolbar = NULL,
  edithandlers = NULL,
  drag = TRUE
)
removeDrawToolbar(map, clearFeatures = FALSE)
```

Arguments

<code>map</code>	The map widget.
<code>targetLayerId</code>	An optional layerId of a GeoJSON/TopoJSON layer whose features need to be editable. Used for adding a GeoJSON/TopoJSON layer and then editing the features using the draw plugin.
<code>targetGroup</code>	An optional group name of a Feature Group whose features need to be editable. Used for adding shapes(markers, lines, polygons) and then editing them using the draw plugin. You can either set layerId or group or none but not both.
<code>position</code>	The position where the toolbar should appear.
<code>polylineOptions</code>	See drawPolylineOptions() . Set to FALSE to disable polyline drawing.
<code>polygonOptions</code>	See drawPolygonOptions() . Set to FALSE to disable polygon drawing.

circleOptions	See drawCircleOptions() . Set to FALSE to disable circle drawing.
rectangleOptions	See drawRectangleOptions() . Set to FALSE to disable rectangle drawing.
markerOptions	See drawMarkerOptions() . Set to FALSE to disable marker drawing.
circleMarkerOptions	See drawCircleMarkerOptions() . Set to FALSE to disable circle marker drawing.
editOptions	By default editing is disable. To enable editing pass editToolbarOptions() .
singleFeature	When set to TRUE, only one feature can be drawn at a time, the previous ones being removed.
toolbar	See toolbarOptions . Set to NULL to take Leaflets default values.
handlers	See handlersOptions . Set to NULL to take Leaflets default values.
edittoolbar	See edittoolbarOptions . Set to NULL to take Leaflets default values.
edithandlers	See edithandlersOptions . Set to NULL to take Leaflets default values.
drag	When set to TRUE, the drawn features will be draggable during editing, utilizing the Leaflet.Draw.Drag plugin. Otherwise, this library will not be included.
clearFeatures	whether to clear the map of drawn features.

Details

The drawn features emit events upon mouse interaction. Event names follow the pattern: `input$MAPID_LAYERCATEGORY_EVENTNAME` where LAYERCATEGORY can be one of:

- marker
- shape
- polyline

Similarly, for EVENTNAME, valid values are:

- click
- mouseover
- mouseout

See the provided example for usage:

```
browseURL(system.file("examples/shiny/draw-events/draw_mouse_events.R", package = "leaflet.extras"))
```

Examples

```
leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addDrawToolbar(
    targetGroup = "draw",
    editOptions = editToolbarOptions(
      selectedPathOptions = selectedPathOptions()
```

```

)
) %>%
addLayersControl(
  overlayGroups = c("draw"),
  options = layersControlOptions(collapsed = FALSE)
) %>%
addStyleEditor()

## for more examples see
# browseURL(system.file("examples/draw.R",
#                         package = "leaflet.extras"))
# browseURL(system.file("examples/shiny/draw-events/app.R",
#                         package = "leaflet.extras"))
# browseURL(system.file("examples/shiny/draw-events/draw_mouse_events.R",
#                         package = "leaflet.extras"))
#

```

addFullscreenControl *Add fullscreen control*

Description

Add a fullscreen control button

Usage

```
addFullscreenControl(map, position = "topleft", pseudoFullscreen = FALSE)
```

Arguments

<code>map</code>	The leaflet map
<code>position</code>	position of control: "topleft", "topright", "bottomleft", or "bottomright"
<code>pseudoFullscreen</code>	if true, fullscreen to page width and height

Examples

```
leaflet() %>%
  addTiles() %>%
  addFullscreenControl()
```

addGeoJSONv2	<i>Adds a GeoJSON/TopoJSON to the leaflet map.</i>
--------------	--

Description

This is a feature rich alternative to the [addGeoJSON](#) & [addTopoJSON](#) with options to map feature properties to labels, popups, colors, markers etc.

Usage

```
addGeoJSONv2(  
  map,  
  geojson,  
  layerId = NULL,  
  group = NULL,  
  markerType = NULL,  
  markerIcons = NULL,  
  markerIconProperty = NULL,  
  markerOptions = leaflet::markerOptions(),  
  clusterOptions = NULL,  
  clusterId = NULL,  
  labelProperty = NULL,  
  labelOptions = leaflet::labelOptions(),  
  popupProperty = NULL,  
  popupOptions = leaflet::popupOptions(),  
  stroke = TRUE,  
  color = "#03F",  
  weight = 5,  
  opacity = 0.5,  
  fill = TRUE,  
  fillColor = color,  
  fillOpacity = 0.2,  
  dashArray = NULL,  
  smoothFactor = 1,  
  noClip = FALSE,  
  pathOptions = leaflet::pathOptions(),  
  highlightOptions = NULL  
)  
  
legendOptions(  
  title = NULL,  
  position = c("bottomleft", "bottomright", "topleft", "topright"),  
  locale = "en-US",  
  numberFormatOptions = list(style = "decimal", maximumFractionDigits = 2)  
)  
  
addGeoJSONChoropleth()
```

```
map,
geojson,
layerId = NULL,
group = NULL,
valueProperty,
labelProperty = NULL,
labelOptions = leaflet::labelOptions(),
popupProperty = NULL,
popupOptions = leaflet::popupOptions(),
scale = c("white", "red"),
steps = 5,
mode = "q",
channelMode = c("rgb", "lab", "hsl", "lch"),
padding = NULL,
correctLightness = FALSE,
bezierInterpolate = FALSE,
colors = NULL,
stroke = TRUE,
color = "#03F",
weight = 1,
opacity = 0.5,
fillOpacity = 0.2,
dashArray = NULL,
smoothFactor = 1,
noClip = FALSE,
pathOptions = leaflet::pathOptions(),
highlightOptions = NULL,
legendOptions = NULL
)
addKML(
map,
kml,
layerId = NULL,
group = NULL,
markerType = NULL,
markerIcons = NULL,
markerIconProperty = NULL,
markerOptions = leaflet::markerOptions(),
clusterOptions = NULL,
clusterId = NULL,
labelProperty = NULL,
labelOptions = leaflet::labelOptions(),
popupProperty = NULL,
popupOptions = leaflet::popupOptions(),
stroke = TRUE,
color = "#03F",
weight = 5,
```

```
    opacity = 0.5,
    fill = TRUE,
    fillColor = color,
    fillOpacity = 0.2,
    dashArray = NULL,
    smoothFactor = 1,
    noClip = FALSE,
    pathOptions = leaflet::pathOptions(),
    highlightOptions = NULL
)

addKMLChoropleth(
  map,
  kml,
  layerId = NULL,
  group = NULL,
  valueProperty,
  labelProperty = NULL,
  labelOptions = leaflet::labelOptions(),
  popupProperty = NULL,
  popupOptions = leaflet::popupOptions(),
  scale = c("white", "red"),
  steps = 5,
  mode = "q",
  channelMode = c("rgb", "lab", "hsl", "lch"),
  padding = NULL,
  correctLightness = FALSE,
  bezierInterpolate = FALSE,
  colors = NULL,
  stroke = TRUE,
  color = "#03F",
  weight = 1,
  opacity = 0.5,
  fillOpacity = 0.2,
  dashArray = NULL,
  smoothFactor = 1,
  noClip = FALSE,
  pathOptions = leaflet::pathOptions(),
  highlightOptions = NULL,
  legendOptions = NULL
)

csvParserOptions(latfield, lonfield, delimiter = ",")

addCSV(
  map,
  csv,
  csvParserOptions,
```

```
layerId = NULL,
group = NULL,
markerType = NULL,
markerIcons = NULL,
markerIconProperty = NULL,
markerOptions = leaflet::markerOptions(),
clusterOptions = NULL,
clusterId = NULL,
labelProperty = NULL,
labelOptions = leaflet::labelOptions(),
popupProperty = NULL,
popupOptions = leaflet::popupOptions(),
stroke = TRUE,
color = "#03F",
weight = 5,
opacity = 0.5,
fill = TRUE,
fillColor = color,
fillOpacity = 0.2,
dashArray = NULL,
smoothFactor = 1,
noClip = FALSE,
pathOptions = leaflet::pathOptions(),
highlightOptions = NULL
)

addGPX(
map,
gpx,
layerId = NULL,
group = NULL,
markerType = NULL,
markerIcons = NULL,
markerIconProperty = NULL,
markerOptions = leaflet::markerOptions(),
clusterOptions = NULL,
clusterId = NULL,
labelProperty = NULL,
labelOptions = leaflet::labelOptions(),
popupProperty = NULL,
popupOptions = leaflet::popupOptions(),
stroke = TRUE,
color = "#03F",
weight = 5,
opacity = 0.5,
fill = TRUE,
fillColor = color,
fillOpacity = 0.2,
```

```

    dashArray = NULL,
    smoothFactor = 1,
    noClip = FALSE,
    pathOptions = leaflet::pathOptions(),
    highlightOptions = NULL
)

```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>geojson</code>	a GeoJSON/TopoJSON URL or file contents in a character vector.
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>markerType</code>	The type of marker. Either <code>marker</code> or <code>circleMarker</code>
<code>markerIcons</code>	Icons for Marker. Can be a single marker using makeIcon or a list of markers using iconList
<code>markerIconProperty</code>	The property of the feature to use for marker icon. Can be a JS function which accepts a feature and returns an index of <code>markerIcons</code> . In either case the result must be one of the indexes of <code>markerIcons</code> .
<code>markerOptions</code>	The options for markers
<code>clusterOptions</code>	if not <code>NULL</code> , markers will be clustered using Leaflet.markercluster ; you can use markerClusterOptions() to specify marker cluster options
<code>clusterId</code>	the id for the marker cluster layer
<code>labelProperty</code>	The property to use for the label. You can also pass in a JS function that takes in a feature and returns a text/HTML content.
<code>labelOptions</code>	A Vector of labelOptions to provide label options for each label. Default <code>NULL</code>
<code>popupProperty</code>	The property to use for popup content You can also pass in a JS function that takes in a feature and returns a text/HTML content.
<code>popupOptions</code>	A Vector of popupOptions to provide popups
<code>stroke</code>	whether to draw stroke along the path (e.g. the borders of polygons or circles)
<code>color</code>	stroke color
<code>weight</code>	stroke width in pixels
<code>opacity</code>	stroke opacity (or layer opacity for tile layers)
<code>fill</code>	whether to fill the path with color (e.g. filling on polygons or circles)
<code>fillColor</code>	fill color
<code>fillOpacity</code>	fill opacity
<code>dashArray</code>	a string that defines the stroke dash pattern

<code>smoothFactor</code>	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
<code>noClip</code>	whether to disable polyline clipping
<code>pathOptions</code>	Options for shapes
<code>highlightOptions</code>	Options for highlighting the shape on mouse over.
<code>title</code>	An optional title for the legend
<code>position</code>	legend position
<code>locale</code>	The numbers will be formatted using this locale
<code>numberFormatOptions</code>	Options for formatting numbers
<code>valueProperty</code>	The property to use for coloring
<code>scale</code>	The scale to use from chroma.js
<code>steps</code>	number of breaks
<code>mode</code>	q for quantile, e for equidistant, k for k-means
<code>channelMode</code>	Default "rgb", can be one of "rgb", "lab", "hsl", "lch"
<code>padding</code>	either a single number or a 2 number vector for clipping color values at ends.
<code>correctLightness</code>	whether to correct lightness
<code>bezierInterpolate</code>	whether to use bezier interpolate for determining colors
<code>colors</code>	overrides scale with manual colors
<code>legendOptions</code>	Options to show a legend.
<code>kml</code>	a KML URL or contents in a character vector.
<code>latfield</code>	field name for latitude
<code>lonfield</code>	field name for longitude
<code>delimiter</code>	field separator
<code>csv</code>	a CSV URL or contents in a character vector.
<code>csvParserOptions</code>	options for parsing the CSV. Use <code>csvParserOptions()</code> to supply csv parser options.
<code>gpx</code>	a GPX URL or contents in a character vector.

Examples

```
## addGeoJSONv2

geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/historic-landmarks-points.geojson"
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
```

```

addProviderTiles(providers$CartoDB.Positron) %>%
addWebGLGeoJSONHeatmap(
  geoJson,
  size = 30, units = "px"
) %>%
addGeoJSONv2(
  geoJson,
  markerType = "circleMarker",
  stroke = FALSE, fillColor = "black", fillOpacity = 0.7,
  markerOptions = markerOptions(radius = 2)
)

## for more examples see
# browseURL(system.file("examples/draw.R", package = "leaflet.extras"))
# browseURL(system.file("examples/geojsonv2.R", package = "leaflet.extras"))
# browseURL(system.file("examples/search.R", package = "leaflet.extras"))
# browseURL(system.file("examples/TopoJSON.R", package = "leaflet.extras"))

## addGeoJSONChoropleth

geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/ward-2012.geojson"
)

leaflet() %>%
addTiles() %>%
setView(-77.0369, 38.9072, 11) %>%
addBootstrapDependency() %>%
enableMeasurePath() %>%
addGeoJSONChoropleth(
  geoJson,
  valueProperty = "AREASQMI",
  scale = c("white", "red"),
  mode = "q",
  steps = 4,
  padding = c(0.2, 0),
  labelProperty = "NAME",
  popupProperty = propstoHTMLTable(
    props = c("NAME", "AREASQMI", "REP_NAME", "WEB_URL", "REP_PHONE", "REP_EMAIL", "REP_OFFICE"),
    table.attrs = list(class = "table table-striped table-bordered"),
    drop.na = TRUE
  ),
  color = "#ffffff", weight = 1, fillOpacity = 0.7,
  highlightOptions = highlightOptions(
    weight = 2, color = "#000000",
    fillOpacity = 1, opacity = 1,
    bringToFront = TRUE, sendToBack = TRUE
  ),
  pathOptions = pathOptions(
    showMeasurements = TRUE,
    measurementOptions = measurementOptions(imperial = TRUE)
)

```

```
)
## for more examples see
# browseURL(system.file("examples/geojsonv2.R", package = "leaflet.extras"))
# browseURL(system.file("examples/measurePath.R", package = "leaflet.extras"))
# browseURL(system.file("examples/search.R", package = "leaflet.extras"))
# browseURL(system.file("examples/TopoJSON.R", package = "leaflet.extras"))

## addKML

kml <- readr::read_file(
  system.file("examples/data/kml/crimes.kml.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addWebGLKMLHeatmap(kml, size = 20, units = "px") %>%
  addKML(
    kml,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1)
  )

## addKMLChoropleth

kml <- readr::read_file(
  system.file("examples/data/kml/cb_2015_us_state_20m.kml.zip", package = "leaflet.extras")
)

leaflet() %>%
  addBootstrapDependency() %>%
  setView(-98.583333, 39.833333, 4) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addKMLChoropleth(
    kml,
    valueProperty = JS(
      "function(feature){
        var props = feature.properties;
        var aland = props.ALAND/100000;
        var awater = props.AWATER/100000;
        return 100*awater/(awater+aland);
      }"
    ),
    scale = "OrRd", mode = "q", steps = 5,
    padding = c(0.2, 0),
    popupProperty = "description",
    labelProperty = "NAME",
    color = "#ffffff", weight = 1, fillOpacity = 1,
    highlightOptions = highlightOptions(

```

```
    fillOpacity = 1, weight = 2, opacity = 1, color = "#000000",
    bringToFront = TRUE, sendToBack = TRUE
),
legendOptions = legendOptions(
  title = "% of Water Area",
  numberFormatOptions = list(
    style = "decimal",
    maximumFractionDigits = 2
  )
)
)

## addCSV

csv <- readr::read_file(
  system.file("examples/data/csv/world_airports.csv.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.DarkMatterNoLabels) %>%
  addCSV(
    csv,
    csvParserOptions("latitude_deg", "longitude_deg"),
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "red", fillOpacity = 1,
    markerOptions = markerOptions(radius = 0.5)
  )

## addGPX

airports <- readr::read_file(
  system.file("examples/data/gpx/md-airports.gpx.zip", package = "leaflet.extras")
)

leaflet() %>%
  addBootstrapDependency() %>%
  setView(-76.6413, 39.0458, 8) %>%
  addProviderTiles(
    providers$CartoDB.Positron,
    options = providerTileOptions(detectRetina = TRUE)
  ) %>%
  addWebGLGPXHeatmap(airports, size = 20000, group = "airports", opacity = 0.9) %>%
  addGPX(
    airports,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1.5),
    group = "airports"
  )
```

```
## for a larger example see
# browseURL(system.file("examples/GPX.R", package = "leaflet.extras"))
```

addGroupedLayersControl

Leaflet layer control with support for grouping overlays together.

Description

Also supports making groups exclusive (using radio inputs instead of checkbox). See the JavaScript plugin for more information <https://github.com/trafficonese/leaflet-groupedlayercontrol/>

Usage

```
addGroupedLayersControl(
  map,
  baseGroups = character(0),
  overlayGroups = character(0),
  position = c("topright", "bottomright", "bottomleft", "topleft"),
  options = groupedLayersControlOptions()
)
```

Arguments

<code>map</code>	the map to add the layers control to
<code>baseGroups</code>	character vector where each element is the name of a group. The user will be able to choose one base group (only) at a time. This is most commonly used for mostly-opaque tile layers.
<code>overlayGroups</code>	A list of named vectors where each element is the name of a group.
<code>position</code>	position of control: "topleft", "topright", "bottomleft", or "bottomright"
<code>options</code>	a list of additional options, intended to be provided by a call to groupedLayersControlOptions

See Also

Other GroupedLayersControl: [addGroupedOverlay\(\)](#), [groupedLayersControlOptions\(\)](#)

Examples

```
library(leaflet)
library(leaflet.extras)

leaflet() %>%
  addTiles(group = "OpenStreetMap") %>%
  addProviderTiles("CartoDB", group = "CartoDB") %>%
  addCircleMarkers(runif(20, -75, -74), runif(20, 41, 42),
```

```

      color = "red", group = "Markers2") %>%
addCircleMarkers(runif(20, -75, -74), runif(20, 41, 42),
                 color="green", group = "Markers1") %>%
addCircleMarkers(runif(20, -75, -74), runif(20, 41, 42),
                 color="yellow", group = "Markers3") %>%
addCircleMarkers(runif(20, -75, -74), runif(20, 41, 42),
                 color = "lightblue", group = "Markers4") %>%
addCircleMarkers(runif(20, -75, -74), runif(20, 41, 42),
                 color = "purple", group = "Markers5") %>%
addGroupedLayersControl(
  baseGroups = c("OpenStreetMap", "CartoDB"),
  overlayGroups = list(
    "Layergroup_2" = c("Markers5", "Markers4"),
    "Layergroup_1" = c("Markers2", "Markers1", "Markers3")),
  position = "topright",
  options = groupedLayersControlOptions(groupCheckboxes = TRUE,
                                         collapsed = FALSE,
                                         groupsCollapsable = TRUE,
                                         sortLayers = FALSE,
                                         sortGroups = FALSE,
                                         sortBaseLayers = FALSE,
                                         exclusiveGroups = "Layergroup_1")
)

```

addGroupedOverlay*Methods of GroupedLayersControl***Description**

- Add an overlay to the GroupedLayersControl
- Add a baselayer to the GroupedLayersControl
- Remove an overlay layer from the GroupedLayersControl
- Removes the GroupedLayersControl from the map

Usage

```

addGroupedOverlay(map, group, name, groupname)

addGroupedBaseLayer(map, group, name)

removeGroupedOverlay(map, group)

removeGroupedLayersControl(map)

```

Arguments

<code>map</code>	The map widget
<code>group</code>	The group of the leaflet layer

<code>name</code>	The visible name of the layer in the control
<code>groupname</code>	The visible group name in the control

See Also

Other GroupedLayersControl: [addGroupedLayersControl\(\)](#), [groupedLayersControlOptions\(\)](#)

<code>addHash</code>	<i>Add dynamic URL Hash</i>
----------------------	-----------------------------

Description

Leaflet-hash lets you to add dynamic URL hashes to web pages with Leaflet maps. You can easily link users to specific map views.

Usage

`addHash(map)`

Arguments

<code>map</code>	The leaflet map
------------------	-----------------

Examples

```
leaflet() %>%
  addTiles() %>%
  addHash()
```

<code>addHeatmap</code>	<i>Add a heatmap</i>
-------------------------	----------------------

Description

Add a heatmap

Adds a heatmap with data from a GeoJSON/TopoJSON file/url

Adds a heatmap with data from a KML file/url

Adds a heatmap with data from a CSV file/url

Adds a heatmap with data from a GPX file/url

removes the heatmap

clears the heatmap

Usage

```
addHeatmap(  
  map,  
  lng = NULL,  
  lat = NULL,  
  intensity = NULL,  
  layerId = NULL,  
  group = NULL,  
  minOpacity = 0.05,  
  max = 1,  
  radius = 25,  
  blur = 15,  
  gradient = NULL,  
  cellSize = NULL,  
  data = leaflet:::getMapData(map)  
)  
  
addGeoJSONHeatmap(  
  map,  
  geojson,  
  layerId = NULL,  
  group = NULL,  
  intensityProperty = NULL,  
  minOpacity = 0.05,  
  max = 1,  
  radius = 25,  
  blur = 15,  
  gradient = NULL,  
  cellSize = NULL  
)  
  
addKMLHeatmap(  
  map,  
  kml,  
  layerId = NULL,  
  group = NULL,  
  intensityProperty = NULL,  
  minOpacity = 0.05,  
  max = 1,  
  radius = 25,  
  blur = 15,  
  gradient = NULL,  
  cellSize = NULL  
)  
  
addCSVHeatmap(  
  map,  
  csv,
```

```

csvParserOptions,
layerId = NULL,
group = NULL,
intensityProperty = NULL,
minOpacity = 0.05,
max = 1,
radius = 25,
blur = 15,
gradient = NULL,
cellSize = NULL
)

addGPXHeatmap(
map,
gpx,
layerId = NULL,
group = NULL,
intensityProperty = NULL,
minOpacity = 0.05,
max = 1,
radius = 25,
blur = 15,
gradient = NULL,
cellSize = NULL
)

removeHeatmap(map, layerId)

clearHeatmap(map)

```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>lng</code>	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
<code>lat</code>	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
<code>intensity</code>	intensity of the heat. A vector of numeric values or a formula.
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>minOpacity</code>	minimum opacity at which the heat will start

max	maximum point intensity. The default is 1.0
radius	radius of each "point" of the heatmap. The default is 25.
blur	amount of blur to apply. The default is 15. blur=1 means no blur.
gradient	palette name from RColorBrewer or an array of colors to be provided to <code>colorNumeric</code> , or a color mapping function returned from <code>colorNumeric</code>
cellSize	the cell size in the grid. Points which are closer than this may be merged. Defaults to 'radius / 2'. Set to '1' to do almost no merging.
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden
geojson	The geojson or topojson url or contents as string.
intensityProperty	The property to use for determining the intensity at a point. Can be a "string" or a JS function, or NULL.
kml	The KML url or contents as string.
csv	The CSV url or contents as string.
csvParserOptions	options for parsing the CSV. Use <code>csvParserOptions()</code> to supply csv parser options.
gpx	The GPX url or contents as string.

Examples

```
leaflet(quakes) %>%
  addProviderTiles(providers$CartoDB.DarkMatter) %>%
  setView(178, -20, 5) %>%
  addHeatmap(
    lng = ~long, lat = ~lat, intensity = ~mag,
    blur = 20, max = 0.05, radius = 15
  )

## for more examples see
# browseURL(system.file("examples/heatmaps.R", package = "leaflet.extras"))
kml <- readr::read_file(
  system.file("examples/data/kml/crimes.kml.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addKMLHeatmap(kml, radius = 7) %>%
  addKML(
    kml,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1)
  )

## for more examples see
# browseURL(system.file("examples/KML.R", package = "leaflet.extras"))
```

`addResetMapButton` *Reset map's view to original view*

Description

Reset map's view to original view

Usage

```
addResetMapButton(map)
```

Arguments

<code>map</code>	The map widget
------------------	----------------

Examples

```
leaflet() %>%
  addTiles() %>%
  addResetMapButton()
```

`addSearchFeatures` *Add a feature search control to the map.*

Description

Add a feature search control to the map.

Removes the feature search control from the map.

Clears the search marker

Usage

```
addSearchFeatures(map, targetGroups, options = searchFeaturesOptions())
removeSearchFeatures(map, clearFeatures = FALSE)
clearSearchFeatures(map)
```

Arguments

<code>map</code>	a map widget object
<code>targetGroups</code>	A vector of group names of groups whose features need to be searched.
<code>options</code>	Search Options
<code>clearFeatures</code>	Boolean. If TRUE the features that this control searches will be removed too.

Value

modified map
modified map
modified map

addSearchOSM	<i>Add a OSM search control to the map.</i>
--------------	---

Description

Add a OSM search control to the map.
Add a OSM search control to the map.
Removes the OSM search control from the map.
Clears the search marker
Add a Google search control to the map.
Removes the Google search control from the map.
Add a US Census Bureau search control to the map.
Removes the US Census Bureau search control from the map.

Usage

```
addSearchOSM(map, options = searchOptions(autoCollapse = TRUE, minLength = 2))

searchOSMText(map, text = "")

removeSearchOSM(map)

clearSearchOSM(map)

addReverseSearchOSM(
  map,
  showSearchLocation = TRUE,
  showBounds = FALSE,
  showFeature = TRUE,
  fitBounds = TRUE,
  displayText = TRUE,
  group = NULL,
  marker = list(icon = NULL),
  showFeatureOptions = list(weight = 2, color = "red", dashArray = "5,10", fillOpacity =
    0.2, opacity = 0.5),
  showBoundsOptions = list(weight = 2, color = "#444444", dashArray = "5,10", fillOpacity =
    0.2, opacity = 0.5),
  showHighlightOptions = list(opacity = 0.8, fillOpacity = 0.5, weight = 5)
```

```

)
addSearchGoogle(
    map,
    apikey = Sys.getenv("GOOGLE_MAP_GEOCODING_KEY"),
    options = searchOptions(autoCollapse = TRUE, minLength = 2)
)
removeSearchGoogle(map)

addReverseSearchGoogle(
    map,
    apikey = Sys.getenv("GOOGLE_MAP_GEOCODING_KEY"),
    showSearchLocation = TRUE,
    showBounds = FALSE,
    showFeature = TRUE,
    fitBounds = TRUE,
    displayText = TRUE,
    group = NULL
)
addSearchUSCensusBureau(
    map,
    options = searchOptions(autoCollapse = TRUE, minLength = 20)
)
removeSearchUSCensusBureau(map)

```

Arguments

<code>map</code>	a map widget object
<code>options</code>	Search Options
<code>text</code>	The search text
<code>showSearchLocation</code>	Boolean. If TRUE displays a Marker on the searched location's coordinates.
<code>showBounds</code>	Boolean. If TRUE show the bounding box of the found feature.
<code>showFeature</code>	Boolean. If TRUE show the found feature. Depending upon the feature found this can be a marker, a line or a polygon.
<code>fitBounds</code>	Boolean. If TRUE set maps bounds to queried and found location. For this to be effective one of <code>showSearchLocation</code> , <code>showBounds</code> , <code>showFeature</code> shoule also be TRUE.
<code>displayText</code>	Boolean. If TRUE show a text box with found location's name on the map.
<code>group</code>	String. An optional group to hold all the searched locations and their results.
<code>marker</code>	Let's you set the icon. Can be an icon made by makeIcon or makeAwesomeIcon
<code>showFeatureOptions</code>	A list of styling options for the found feature

```
showBoundsOptions  
  A list of styling options for the bounds of the found feature  
showHighlightOptions  
  A list of styling options for the hover effect of a found feature  
apikey      String. API Key for Google GeoCoding Service.
```

Value

```
modified map  
modified map
```

Examples

```
leaflet() %>%  
  addProviderTiles(providers$Esri.WorldStreetMap) %>%  
  addResetMapButton() %>%  
  addSearchGoogle()  
  
## for more examples see  
# browseURL(system.file("examples/search.R", package = "leaflet.extras"))
```

```
addStyleEditor
```

*Add style editor***Description**

Add style editor

Remove style editor

Usage

```
addStyleEditor(
  map,
  position = c("topleft", "topright", "bottomleft", "bottomright"),
  openOnLeafletDraw = TRUE,
  useGrouping = FALSE,
  ...
)
removeStyleEditor(map)
```

Arguments

<code>map</code>	the map widget
<code>position</code>	position of the control
<code>openOnLeafletDraw</code>	whether to open automatically when used with <code>addDrawToolbar()</code>
<code>useGrouping</code>	Should be false to work with <code>addDrawToolbar()</code>
<code>...</code>	other options. See plugin code

Examples

```
leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addDrawToolbar(
    targetGroup = "draw",
    editOptions = editToolbarOptions(selectedPathOptions = selectedPathOptions())
  ) %>%
  addLayersControl(
    overlayGroups = c("draw"), options = layersControlOptions(collapsed = FALSE)
  ) %>%
  # add the style editor to alter shapes added to map
  addStyleEditor()
```

`addWebGLHeatmap` *Add a webgl heatmap*

Description

Add a webgl heatmap

Adds a heatmap with data from a GeoJSON/TopoJSON file/url

Adds a heatmap with data from a KML file/url

Adds a heatmap with data from a CSV file/url

Adds a heatmap with data from a GPX file/url

removes the webgl heatmap

clears the webgl heatmap

Usage

```
addWebGLHeatmap(  
    map,  
    lng = NULL,  
    lat = NULL,  
    intensity = NULL,  
    layerId = NULL,  
    group = NULL,  
    size = "30000",  
    units = "m",  
    opacity = 1,  
    gradientTexture = NULL,  
    alphaRange = 1,  
    data = leaflet::getMapData(map)  
)  
  
addWebGLGeoJSONHeatmap(  
    map,  
    geojson,  
    layerId = NULL,  
    group = NULL,  
    intensityProperty = NULL,  
    size = "30000",  
    units = "m",  
    opacity = 1,  
    gradientTexture = NULL,  
    alphaRange = 1  
)  
  
addWebGLKMLHeatmap(  
    map,  
    kml,  
    layerId = NULL,  
    group = NULL,  
    intensityProperty = NULL,  
    size = "30000",  
    units = "m",  
    opacity = 1,  
    gradientTexture = NULL,  
    alphaRange = 1  
)  
  
addWebGLCSVHeatmap(  
    map,  
    csv,  
    csvParserOptions,  
    layerId = NULL,  
    group = NULL,
```

```

intensityProperty = NULL,
size = "30000",
units = "m",
opacity = 1,
gradientTexture = NULL,
alphaRange = 1
)

addWebGLGPXHeatmap(
  map,
  gpx,
  layerId = NULL,
  group = NULL,
  intensityProperty = NULL,
  size = "30000",
  units = "m",
  opacity = 1,
  gradientTexture = NULL,
  alphaRange = 1
)

removeWebGLHeatmap(map, layerId)

clearWebGLHeatmap(map)

```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>lng</code>	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in <code>data</code> ; by default (if not explicitly provided), it will be automatically inferred from <code>data</code> by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
<code>lat</code>	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
<code>intensity</code>	intensity of the heat. A vector of numeric values or a formula.
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>size</code>	in meters or pixels
<code>units</code>	either "m" or "px"
<code>opacity</code>	for the canvas element
<code>gradientTexture</code>	Alternative colors for heatmap. allowed values are "skyline", "deep-sea"

alphaRange	adjust transparency by changing to value between 0 and 1
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden
geojson	The geojson or topojson url or contents as string.
intensityProperty	The property to use for determining the intensity at a point. Can be a "string" or a JS function, or NULL.
kml	The KML url or contents as string.
csv	The CSV url or contents as string.
csvParserOptions	options for parsing the CSV. Use <code>csvParserOptions()</code> to supply csv parser options.
gpx	The GPX url or contents as string.

Examples

```
## addWebGLHeatmap
leaflet(quakes) %>%
  addProviderTiles(providers$CartoDB.DarkMatter) %>%
  addWebGLHeatmap(lng = ~long, lat = ~lat, size = 60000)

## for more examples see
# browseURL(system.file("examples/webglHeatmaps.R", package = "leaflet.extras"))
## addWebGLGeoJSONHeatmap

geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/historic-landmarks-points.geojson"
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addWebGLGeoJSONHeatmap(
    geoJson,
    size = 30, units = "px"
  ) %>%
  addGeoJSONv2(
    geoJson,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 0.7,
    markerOptions = markerOptions(radius = 2)
  )

## for more examples see
# browseURL(system.file("examples/geojsonV2.R", package = "leaflet.extras"))
# browseURL(system.file("examples/TopoJSON.R", package = "leaflet.extras"))
## addWebGLKMLHeatmap

kml <- readr::read_file(
```

```

system.file("examples/data/kml/crimes.kml.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(-77.0369, 38.9072, 12) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addWebGLKMLHeatmap(kml, size = 20, units = "px") %>%
  addKML(
    kml,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
    markerOptions = markerOptions(radius = 1)
  )

## addWebGLCSVHeatmap

csv <- readr::read_file(
  system.file("examples/data/csv/world_airports.csv.zip", package = "leaflet.extras")
)

leaflet() %>%
  setView(0, 0, 2) %>%
  addProviderTiles(providers$CartoDB.DarkMatterNoLabels) %>%
  addWebGLCSVHeatmap(
    csv,
    csvParserOptions("latitude_deg", "longitude_deg"),
    size = 10, units = "px"
  )

airports <- readr::read_file(
  system.file("examples/data/gpx/md-airports.gpx.zip", package = "leaflet.extras")
)

leaflet() %>%
  addBootstrapDependency() %>%
  setView(-76.6413, 39.0458, 8) %>%
  addProviderTiles(
    providers$CartoDB.Positron,
    options = providerTileOptions(detectRetina = TRUE)
  ) %>%
  addWebGLGPXHeatmap(
    airports,
    size = 20000,
    group = "airports",
    opacity = 0.9
  ) %>%
  addGPX(
    airports,
    markerType = "circleMarker",
    stroke = FALSE, fillColor = "black", fillOpacity = 1,
  )

```

```

    markerOptions = markerOptions(radius = 1.5),
    group = "airports"
)

## for a larger example see
# browseURL(system.file("examples/GPX.R", package = "leaflet.extras"))

```

addWMSLegend*Add WMS Legend***Description**

Add a WMS Legend

Usage

```

addWMSLegend(
  map,
  uri,
  position = "topright",
  layerId = NULL,
  group = NULL,
  title = "",
  titleClass = "wms-legend-title",
  titleStyle = ""
)

```

Arguments

map	a map widget object created from leaflet()
uri	The legend URI
position	the position of the legend
layerId	When the layerId of the WMS layer is properly set, the legend will appear or disappear accordingly based on whether the layer is visible or not. If no layerId is given, it will try to get the layer name from the ‘uri’, otherwise a random ID will be assigned.
group	The group argument is not used. Please set the ‘layerId’ correctly.
title	A title that is prepended before the image.
titleClass	CSS-class for the title div
titleStyle	Style the title with CSS

Examples

```
leaflet() %>%
  addTiles() %>%
  setView(11, 51, 6) %>%
  addWMSTiles(
    baseUrl = "https://www.wms.nrw.de/wms/unfallatlas?request=GetMap",
    layers = c("Unfallorte", "Personenschaden_5000", "Personenschaden_250"),
    options = WMSTileOptions(format = "image/png", transparent = TRUE)
  ) %>%
  addWMSLegend(
    title = "Personenschaden_5000", titleStyle = "font-size:1em; font-weight:800",
    uri = paste0(
      "https://www.wms.nrw.de/wms/unfallatlas?request=",
      "GetLegendGraphic&version=1.3.0&",
      "format=image/png&layer=Personenschaden_5000"
    )
  )
)
```

`debugMap`

For debugging a leaflet map

Description

For debugging a leaflet map

Usage

```
debugMap(map)
```

Arguments

<code>map</code>	The map widget
------------------	----------------

`drawShapeOptions`

Options for drawn shapes

Description

- Options for drawn shapes
- Options for drawing polylines
- Options for drawing polygons
- Options for drawing rectangles
- Options for drawing Circles
- Options for drawing markers
- Options for drawing markers
- Options for path when in editMode
- Options for editing shapes

Usage

```
drawShapeOptions(  
  stroke = TRUE,  
  color = "#03f",  
  weight = 1,  
  opacity = 1,  
  fill = TRUE,  
  fillColor = "#03f",  
  fillOpacity = 0.4,  
  dashArray = NULL,  
  lineCap = NULL,  
  lineJoin = NULL,  
  clickable = TRUE,  
  pointerEvents = NULL,  
  smoothFactor = 1,  
  noClip = TRUE  
)  
  
drawPolylineOptions(  
  allowIntersection = TRUE,  
  drawError = list(color = "#b00b00", timeout = 2500),  
  guidelineDistance = 20,  
  maxGuideLineLength = 4000,  
  showLength = TRUE,  
  metric = TRUE,  
  feet = TRUE,  
  nautic = FALSE,  
  zIndexOffset = 2000,  
  shapeOptions = drawShapeOptions(fill = FALSE),  
  repeatMode = FALSE  
)  
  
drawPolygonOptions(  
  showArea = FALSE,  
  metric = TRUE,  
  shapeOptions = drawShapeOptions(),  
  repeatMode = FALSE  
)  
  
drawRectangleOptions(  
  showArea = TRUE,  
  metric = TRUE,  
  shapeOptions = drawShapeOptions(),  
  repeatMode = FALSE  
)  
  
drawCircleOptions(  
  showRadius = TRUE,
```

```

metric = TRUE,
feet = TRUE,
nautic = FALSE,
shapeOptions = drawShapeOptions(),
repeatMode = FALSE
)

drawMarkerOptions(markerIcon = NULL, zIndexOffset = 2000, repeatMode = FALSE)

drawCircleMarkerOptions(
  stroke = TRUE,
  color = "#3388ff",
  weight = 4,
  opacity = 0.5,
  fill = TRUE,
  fillColor = NULL,
  fillOpacity = 0.2,
  clickable = TRUE,
  zIndexOffset = 2000,
  repeatMode = FALSE
)

selectedPathOptions(
  dashArray = c("10, 10"),
  weight = 2,
  color = "black",
  fill = TRUE,
  fillColor = "black",
  fillOpacity = 0.6,
  maintainColor = FALSE
)

editToolbarOptions(
  edit = TRUE,
  remove = TRUE,
  selectedPathOptions = NULL,
  allowIntersection = TRUE
)

```

Arguments

<code>stroke</code>	Whether to draw stroke along the path. Set it to false to disable borders on polygons or circles.
<code>color</code>	Stroke color.
<code>weight</code>	Stroke width in pixels.
<code>opacity</code>	Stroke opacity.
<code>fill</code>	Whether to fill the path with color. Set it to false to disable filling on polygons or circles.

fillColor	same as color Fill color.
fillOpacity	Fill opacity.
dashArray	A string that defines the stroke dash pattern. Doesn't work on canvas-powered layers (e.g. Android 2).
lineCap	A string that defines shape to be used at the end of the stroke.
lineJoin	A string that defines shape to be used at the corners of the stroke.
clickable	If false, the vector will not emit mouse events and will act as a part of the underlying map.
pointerEvents	Sets the pointer-events attribute on the path if SVG backend is used.
smoothFactor	How much to simplify the polyline on each zoom level. More means better performance and smoother look, and less means more accurate representation.
noClip	Disabled polyline clipping.
allowIntersection	Determines if line segments can cross.
drawError	Configuration options for the error that displays if an intersection is detected.
guidelineDistance	Distance in pixels between each guide dash.
maxGuideLineLength	Maximum length of the guide lines.
showLength	Whether to display the distance in the tooltip.
metric	Determines which measurement system (metric or imperial) is used.
feet	When not metric, use feet instead of yards for display.
nautic	When not metric, not feet, use nautic mile for display.
zIndexOffset	This should be a high number to ensure that you can draw over all other layers on the map.
shapeOptions	Leaflet Polyline options See drawShapeOptions() .
repeatMode	Determines if the draw tool remains enabled after drawing a shape.
showArea	Show the area of the drawn polygon in m ² , ha or km ² . The area is only approximate and become less accurate the larger the polygon is.
showRadius	Show the radius of the drawn circle in m, km, ft (feet), or nm (nautical mile).
markerIcon	Can be either makeIcon() OR makeAwesomeIcon
maintainColor	Whether to maintain shape's original color
edit	Editing enabled by default. Set to false do disable editing.
remove	Set to false to disable removing.
selectedPathOptions	To customize shapes in editing mode pass selectedPathOptions() .

edithandlersOptions *Options for editing edit handlers*

Description

Customize edit handlers for [addDrawToolbar](#)

Usage

```
edithandlersOptions(
  edit = list(tooltipText = "Drag handles or markers to edit features.", tooltipSubtext =
    "Click cancel to undo changes."),
  remove = list(tooltipText = "Click on a feature to remove.")
)
```

Arguments

edit	List of options for editing tooltips.
remove	List of options for removing tooltips.

edittoolbarOptions *Options for editing the toolbar*

Description

Customize the edit toolbar for [addDrawToolbar](#)

Usage

```
edittoolbarOptions(
  actions = list(save = list(title = "Save changes", text = "Save"), cancel = list(title =
    "Cancel editing, discards all changes", text = "Cancel"), clearAll = list(title =
    "Clear all layers", text = "Clear All")),
  buttons = list(edit = "Edit layers", editDisabled = "No layers to edit", remove =
    "Delete layers", removeDisabled = "No layers to delete")
)
```

Arguments

actions	List of options for edit action tooltips.
buttons	List of options for edit button tooltips.

enableMeasurePath	<i>Enables measuring of length of polylines and areas of polygons</i>
-------------------	---

Description

Enables measuring of length of polylines and areas of polygons
 Options for measure-path
 Adds a toolbar to enable/disable measuring path distances/areas

Usage

```
enableMeasurePath(map)

measurePathOptions(
  showOnHover = FALSE,
  minPixelDistance = 30,
  showDistances = TRUE,
  showArea = TRUE,
  imperial = FALSE
)
addMeasurePathToolbar(map, options = measurePathOptions())
```

Arguments

map	The map widget.
showOnHover	If TRUE, the measurements will only show when the user hovers the cursor over the path.
minPixelDistance	The minimum length a line segment in the feature must have for a measurement to be added.
showDistances	If FALSE, doesn't show distances along line segments of of a polyline/polygon.
showArea	If FALSE, doesn't show areas of a polyline/polygon.
imperial	If TRUE the distances/areas will be shown in imperial units.
options	The measurePathOptions.

Examples

```
geoJson <- readr::read_file(
  "https://rawgit.com/benbalter/dc-maps/master/maps/ward-2012.geojson"
)

leaflet() %>%
  addTiles() %>%
  setView(-77.0369, 38.9072, 11) %>%
```

```

addBootstrapDependency() %>%
enableMeasurePath() %>%
addGeoJSONChoropleth(
  geoJson,
  valueProperty = "AREASQMI",
  scale = c("white", "red"),
  mode = "q",
  steps = 4,
  padding = c(0.2, 0),
  labelProperty = "NAME",
  popupProperty = propstoHTMLTable(
    props = c("NAME", "AREASQMI", "REP_NAME", "WEB_URL", "REP_PHONE", "REP_EMAIL", "REP_OFFICE"),
    table.attrs = list(class = "table table-striped table-bordered"),
    drop.na = TRUE
  ),
  color = "#ffffff", weight = 1, fillOpacity = 0.7,
  highlightOptions = highlightOptions(
    weight = 2, color = "#000000",
    fillOpacity = 1, opacity = 1,
    bringToFront = TRUE, sendToBack = TRUE
  ),
  pathOptions = pathOptions(
    showMeasurements = TRUE,
    measurementOptions = measurePathOptions(imperial = TRUE)
  )
)
)

```

`enableTileCaching` *Enables caching of Tiles*

Description

Enables caching of tiles locally in browser. See <https://github.com/MazeMap/Leaflet.TileLayer.PouchDBCached> for details. In addition to invoking this function, you should also pass `useCache=TRUE & crossOrigin=TRUE` in the `tileOptions` call and pass that to your `addTiles`'s options parameter.

Usage

```
enableTileCaching(map)
```

Arguments

map	The leaflet map
-----	-----------------

Examples

```
leaflet() %>%
  enableTileCaching() %>%
  addTiles(options = tileOptions(useCache = TRUE, crossOrigin = TRUE))

## for more examples see
# browseURL(system.file("examples/TileLayer-Caching.R", package = "leaflet.extras"))
```

geodesics

Add Geodesic Lines & Circles

Description

A geodesic line is the shortest path between two given positions on the earth surface. It's based on Vincenty's formulae implemented by [Chris Veness](#) for highest precision.

Add Lat/Long to a Geodesic Polyline.

Adds a Great Circle to the map.

Usage

```
addGeodesicPolylines(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  steps = 10,
  wrap = TRUE,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  dashArray = NULL,
  smoothFactor = 1,
  noClip = FALSE,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  options = pathOptions(),
  highlightOptions = NULL,
  icon = NULL,
  showMarker = FALSE,
  showStats = FALSE,
  statsFunction = NULL,
  markerOptions = NULL,
```

```

    data = getMapData(map)
)

addLatLng(map, lat, lng, layerId = NULL)

addGreatCircles(
  map,
  lat_center = NULL,
  lng_center = NULL,
  radius,
  layerId = NULL,
  group = NULL,
  steps = 10,
  wrap = TRUE,
  stroke = TRUE,
  color = "#03F",
  weight = 5,
  opacity = 0.5,
  dashArray = NULL,
  smoothFactor = 1,
  noClip = FALSE,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  options = pathOptions(),
  highlightOptions = NULL,
  icon = NULL,
  fill = TRUE,
  showMarker = FALSE,
  showStats = FALSE,
  statsFunction = NULL,
  markerOptions = NULL,
  data = getMapData(map)
)

```

Arguments

<code>map</code>	a map widget object created from leaflet()
<code>lat, lng</code>	lat/lng to add to the Geodesic
<code>layerId</code>	the layer id
<code>group</code>	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
<code>steps</code>	Defines how many intermediate points are generated along the path. More steps mean a smoother path.

<code>wrap</code>	Wrap line at map border (date line). Set to "false" if you want lines to cross the dateline (experimental, see noWrap-example on how to use)
<code>stroke</code>	whether to draw stroke along the path (e.g. the borders of polygons or circles)
<code>color</code>	stroke color
<code>weight</code>	stroke width in pixels
<code>opacity</code>	stroke opacity (or layer opacity for tile layers)
<code>dashArray</code>	a string that defines the stroke dash pattern
<code>smoothFactor</code>	how much to simplify the polyline on each zoom level (more means better performance and less accurate representation)
<code>noClip</code>	whether to disable polyline clipping
<code>popup</code>	a character vector of the HTML content for the popups (you are recommended to escape the text using htmlEscape() for security reasons)
<code>popupOptions</code>	A Vector of popupOptions to provide popups
<code>label</code>	a character vector of the HTML content for the labels
<code>labelOptions</code>	A Vector of labelOptions to provide label options for each label. Default NULL
<code>options</code>	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
<code>highlightOptions</code>	Options for highlighting the shape on mouse over.
<code>icon</code>	the icon(s) for markers; an icon is represented by an R list of the form <code>list(iconUrl = "?", iconSize = c(x, y))</code> , and you can use icons() to create multiple icons; note when you use an R list that contains images as local files, these local image files will be base64 encoded into the HTML page so the icon images will still be available even when you publish the map elsewhere
<code>showMarker</code>	Should the nodes/center points be visualized as Markers?
<code>showStats</code>	This will create an L.Control with some information on the geodesics
<code>statsFunction</code>	A custom JS function to be showed in the info control
<code>markerOptions</code>	List of options for the markers. See markerOptions
<code>data</code>	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden
<code>lat_center, lng_center</code>	lat/lng for the center
<code>radius</code>	in meters
<code>fill</code>	whether to fill the path with color (e.g. filling on polygons or circles)

Examples

```
berlin <- c(52.51, 13.4)
losangeles <- c(34.05, -118.24)
santiago <- c(-33.44, -70.71)
tokio <- c(35.69, 139.69)
sydney <- c(-33.91, 151.08)
capetown <- c(-33.91, 18.41)
```

```

calgary <- c(51.05, -114.08)
hammerfest <- c(70.67, 23.68)
barrow <- c(71.29, -156.76)

df <- as.data.frame(rbind(hammerfest, calgary, losangeles, santiago, capetown, tokio, barrow))
names(df) <- c("lat", "lng")

leaflet(df) %>%
  addProviderTiles(providers$CartoDB.Positron) %>%
  addGeodesicPolylines(
    lng = ~lng, lat = ~lat, weight = 2, color = "red",
    steps = 50, opacity = 1
  ) %>%
  addCircleMarkers(df,
    lat = ~lat, lng = ~lng, radius = 3, stroke = FALSE,
    fillColor = "black", fillOpacity = 1
  )

## for more examples see
# browseURL(system.file("examples/geodesic.R", package = "leaflet.extras"))

```

gpsOptions*Options for the GPS Control***Description**

Options for the GPS Control

Add a gps to the Map.

Removes the GPS Control

Activate the GPS Control. You should have already added the GPS control before calling this method.

Deactivate the GPS Control. You should have already added the GPS control before calling this method.

Usage

```

gpsOptions(
  position = "topleft",
  activate = FALSE,
  autoCenter = FALSE,
  maxZoom = NULL,
  setView = FALSE
)

addControlGPS(map, options = gpsOptions())

removeControlGPS(map)

```

```
activateGPS(map)  
deactivateGPS(map)
```

Arguments

position	Position of the Control
activate	If TRUE activates the GPS on addition.
autoCenter	If TRUE auto centers the map when GPS location changes
maxZoom	If set zooms to this level when auto centering
setView	If TRUE sets the view to the GPS location when found
map	a map widget object
options	Options for the GPS control.

Examples

```
leaflet() %>%  
  addTiles() %>%  
  addControlGPS()
```

groupedLayersControlOptions

Options for the GroupedLayersControl

Description

Options for the GroupedLayersControl

Usage

```
groupedLayersControlOptions(  
  exclusiveGroups = NULL,  
  groupCheckboxes = TRUE,  
  groupsCollapsible = TRUE,  
  groupsExpandedClass = "leaflet-control-layers-group-collapse-default",  
  groupsCollapsedClass = "leaflet-control-layers-group-expand-default",  
  sortLayers = FALSE,  
  sortGroups = FALSE,  
  sortBaseLayers = FALSE,  
  collapsed = TRUE,  
  autoZIndex = TRUE,  
  ...  
)
```

Arguments

<code>exclusiveGroups</code>	character vector of layer groups to make exclusive (use radio buttons)
<code>groupCheckboxes</code>	Show a checkbox next to non-exclusive group labels for toggling all
<code>groupsCollapsable</code>	Should groups be collapsible? Default is TRUE
<code>groupsExpandedClass</code>	The CSS class of expanded groups
<code>groupsCollapsedClass</code>	The CSS class of collapsed groups
<code>sortLayers</code>	Sort the overlay layers alphabetically? Default is FALSE
<code>sortGroups</code>	Sort the groups alphabetically? Default is FALSE
<code>sortBaseLayers</code>	Sort the baselayers alphabetically? Default is FALSE
<code>collapsed</code>	if TRUE (the default), the layers control will be rendered as an icon that expands when hovered over. Set to FALSE to have the layers control always appear in its expanded state.
<code>autoZIndex</code>	if TRUE, the control will automatically maintain the z-order of its various groups as overlays are switched on and off.
<code>...</code>	other options for <code>layersControlOptions()</code>

See Also

Other GroupedLayersControl: [addGroupedLayersControl\(\)](#), [addGroupedOverlay\(\)](#)

`handlersOptions` *Options for editing handlers*

Description

Customize tooltips for [addDrawToolbar](#)

Usage

```
handlersOptions(
  polyline = list(error = "<strong>Error:</strong> shape edges cannot cross!",
    tooltipStart = "Click to start drawing line.", tooltipCont =
    "Click to start drawing line.", tooltipEnd = "Click to start drawing line."),
  polygon = list(tooltipStart = "Click to start drawing shape.", tooltipCont =
    "Click to start drawing shape.", tooltipEnd = "Click to start drawing shape."),
  rectangle = list(tooltipStart = "Click and drag to draw rectangle."),
  circle = list(tooltipStart = "Click map to place circle marker.", radius = "Radius"),
  marker = list(tooltipStart = "Click map to place marker."),
  circlemarker = list(tooltipStart = "Click and drag to draw circle."),
  simpleshape = list(tooltipEnd = "Release mouse to finish drawing."))
)
```

Arguments

polyline	List of options for polyline tooltips.
polygon	List of options for polygon tooltips.
rectangle	List of options for rectangle tooltips.
circle	List of options for circle tooltips.
marker	List of options for marker tooltips.
circlemarker	List of options for circlemarker tooltips.
simpleshape	List of options for simpleshape tooltips.

Examples

```
## Not run:
library(leaflet)
library(leaflet.extras)
leaflet() %>%
  addTiles() %>%
  addDrawToolbar(
    handlers = handlersOptions(
      polyline = list(
        tooltipStart = "Click It",
        tooltipCont = "Keep going",
        tooltipEnd = "Make it stop"
      ),
      polylineOptions = T, rectangleOptions = F, circleOptions = F,
      polygonOptions = F, markerOptions = F, circlemarkerOptions = F
    )
  )
## End(Not run)
```

leafletExtrasDependencies

Various leaflet dependency functions for use in downstream packages

Description

Various leaflet dependency functions for use in downstream packages

Usage

`leafletExtrasDependencies`

Format

An object of class `list` of length 5.

*propsToHTML**Converts GeoJSON Feature properties to HTML*

Description

- Converts GeoJSON Feature properties to HTML
- Converts GeoJSON Feature properties to HTML Table.
- Customize the leaflet widget style

Usage

```
propsToHTML(props, elem = NULL, elem.attrs = NULL)

propstoHTMLTable(props = NULL, table.attrs = NULL, drop.na = TRUE)

setMapWidgetStyle(map, style = list(background = "transparent"))
```

Arguments

props	A list of GeoJSON Property Keys.
elem	An optional wrapping element e.g. "div".
elem.attrs	An optional named list for the wrapper element properties.
table.attrs	An optional named list for the HTML Table.
drop.na	whether to skip properties with empty values.
map	the map widget
style	a A list of CSS key/value properties.

Examples

```
geoJson <- jsonlite::fromJSON(readr::read_file(
  paste0(
    "https://raw.githubusercontent.com/MinnPost/simple-map-d3",
    "/master/example-data/world-population.geo.json"
  )
))

world <- leaflet(
  options = leafletOptions(
    maxZoom = 5,
    crs = leafletCRS(
      crsClass = "L.Proj.CRS", code = "ESRI:53009",
      proj4def = "+proj=moll +lon_0=0 +x_0=0 +y_0=0 +a=6371000 +b=6371000 +units=m +no_defs",
      resolutions = c(65536, 32768, 16384, 8192, 4096, 2048)
    )
  )
) %>%
```

```
addGraticule(style = list(color = "#999", weight = 0.5, opacity = 1, fill = NA)) %>%  
addGraticule(sphere = TRUE, style = list(color = "#777", weight = 1, opacity = 0.25, fill = NA))  
  
world  
  
# change background to white  
world %>%  
  setMapWidgetStyle(list(background = "white"))
```

pulseIconList*Make pulse-icon set*

Description

An icon can be represented as a list of the form `list(color, iconSize, ...)`. This function is vectorized over its arguments to create a list of icon data. Shorter argument values will be re-cycled. NULL values for these arguments will be ignored.

Usage

```
pulseIconList(...)  
  
## S3 method for class 'leaflet_pulse_icon_set'  
x[i]  
  
makePulseIcon(color = "#ff0000", iconSize = 12, animate = TRUE, heartbeat = 1)  
  
pulseIcons(color = "#ff0000", iconSize = 12, animate = TRUE, heartbeat = 1)  
  
addPulseMarkers(  
  map,  
  lng = NULL,  
  lat = NULL,  
  layerId = NULL,  
  group = NULL,  
  icon = NULL,  
  popup = NULL,  
  popupOptions = NULL,  
  label = NULL,  
  labelOptions = NULL,  
  options = leaflet::markerOptions(),  
  clusterOptions = NULL,  
  clusterId = NULL,  
  data = leaflet::getMapData(map)  
)
```

Arguments

...	icons created from makePulseIcon()
x	icons
i	offset
color	Color of the icon
iconSize	Size of Icon in Pixels.
animate	To animate the icon or not, defaults to TRUE.
heartbeat	Interval between each pulse in seconds.
map	a map widget object created from leaflet()
lng	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named lng, long, or longitude (case-insensitively)
lat	a vector of latitudes or a formula (similar to the lng argument; the names lat and latitude are used when guessing the latitude column from data)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for clearGroup and addLayersControl purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
icon	the icon(s) for markers; an icon is represented by an R list of the form <code>list(iconUrl = "?", iconSize = c(x, y))</code> , and you can use icons() to create multiple icons; note when you use an R list that contains images as local files, these local image files will be base64 encoded into the HTML page so the icon images will still be available even when you publish the map elsewhere
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using htmlEscape() for security reasons)
popupOptions	A Vector of popupOptions to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of labelOptions to provide label options for each label. Default NULL
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
clusterOptions	if not NULL, markers will be clustered using Leaflet.markercluster ; you can use markerClusterOptions() to specify marker cluster options
clusterId	the id for the marker cluster layer
data	the data object from which the argument values are derived; by default, it is the data object provided to leaflet() initially, but can be overridden

Examples

```
iconSet <- pulseIconList(  
  red = makePulseIcon(color = "#ff0000"),  
  blue = makePulseIcon(color = "#0000ff"))  
)  
  
iconSet[c("red", "blue")]  
  
leaflet() %>%  
  addTiles() %>%  
  addPulseMarkers(  
    lng = -118.456554, lat = 34.078039,  
    label = "This is a label",  
    icon = makePulseIcon(heartbeat = 0.5)  
)  
  
## for more examples see  
# browseURL(system.file("examples/pulseIcon.R", package = "leaflet.extras"))
```

searchOptions *Options for search control.*

Description

Options for search control.

Customized searchOptions for Feature Search

Usage

```
searchOptions(  
  url = NULL,  
  sourceData = NULL,  
  jsonParam = NULL,  
  propertyLoc = NULL,  
  propertyName = NULL,  
  formatData = NULL,  
  filterData = NULL,  
  moveToLocation = TRUE,  
  zoom = 17,  
  buildTip = NULL,  
  container = "",  
  minLength = 1,  
  initial = TRUE,  
  casesensitive = FALSE,  
  autoType = TRUE,  
  delayType = 400,  
  tooltipLimit = -1,
```

```

tipAutoSubmit = TRUE,
firstTipSubmit = FALSE,
autoResize = TRUE,
collapsed = TRUE,
autoCollapse = FALSE,
autoCollapseTime = 1200,
textErr = "Location Not Found",
textCancel = "Cancel",
textPlaceholder = "Search...",
position = "topleft",
hideMarkerOnCollapse = FALSE,
marker = list(icon = NULL, animate = TRUE, circle = list(radius = 10, weight = 3, color
= "#e03", stroke = TRUE, fill = FALSE))
)

searchFeaturesOptions(
  propertyName = "label",
  initial = FALSE,
  openPopup = FALSE,
  ...
)

```

Arguments

url	url for search by ajax request, ex: ‘search.php?q={s}’. Can be function that returns string for dynamic parameter setting.
sourceData	function that fill _recordsCache, passed searching text by first param and callback in second.
jsonpParam	jsonp param name for search by jsonp service, ex: "callback".
propertyLoc	field for remapping location, using array: ["latname", "lonname"] for select double fields(ex. ["lat", "lon"]) support dotted format: "prop.subprop.title".
propertyName	property in marker.options(or feature.properties for vector layer) trough filter elements in layer,
formatData	callback for reformat all data from source to indexed data object.
filterData	callback for filtering data from text searched, params: textSearch, allRecords.
moveToLocation	whether to move to the found location.
zoom	zoom to this level when moving to location
buildTip	function that return row tip html node(or html string), receive text tooltip in first param.
container	container id to insert Search Control.
minLength	minimal text length for autocomplete.
initial	search elements only by initial text.
casesensitive	search elements in case sensitive text.
autoType	complete input with first suggested result and select this filled-in text..

```

delayType      delay while typing for show tooltip.
tooltipLimit   limit max results to show in tooltip. -1 for no limit..
tipAutoSubmit  auto map panTo when click on tooltip.
firstTipSubmit auto select first result con enter click.
autoResize     autoresize on input change.
collapsed      collapse search control at startup.
autoCollapse   collapse search control after submit(on button or on tips if enabled tipAutoSubmit).
autoCollapseTime
               delay for autoclosing alert and collapse after blur.
textErr        'Location not error message.
textCancel     title in cancel button.
textPlaceholder
               placeholder value.
position       "topleft".
hideMarkerOnCollapse
               remove circle and marker on search control collapsed.
marker         Let's you set the icon. Can be an icon made by makeIcon or makeAwesomeIcon
openPopup      whether to open the popup associated with the feature when the feature is searched
               for
...
               Other options to pass to searchOptions\(\) function.

```

suspendScroll*Prevents accidental map scrolling when scrolling in a document.***Description**

Prevents accidental map scrolling when scrolling in a document.

Usage

```

suspendScroll(
  map,
  sleep = TRUE,
  sleepTime = 750,
  wakeTime = 750,
  sleepNote = TRUE,
  hoverToWake = TRUE,
  wakeMessage = "Click or Hover to Wake",
  sleepOpacity = 0.7
)

```

Arguments

<code>map</code>	The leaflet map
<code>sleep</code>	false if you want an unruly map
<code>sleepTime</code>	time(ms) until map sleeps on mouseout
<code>wakeTime</code>	time(ms) until map wakes on mouseover
<code>sleepNote</code>	should the user receive wake instructions?
<code>hoverToWake</code>	should hovering wake the map? (non-touch devices only)
<code>wakeMessage</code>	a message to inform users about waking the map
<code>sleepOpacity</code>	opacity for the sleeping map

Examples

```
leaflet(width = "100%") %>%
  setView(0, 0, 1) %>%
  addTiles() %>%
  suspendScroll()
```

`toolbarOptions`

Options for editing the toolbar

Description

Customize the toolbar for [addDrawToolbar](#)

Usage

```
toolbarOptions(
  actions = list(title = "Cancel drawing", text = "Cancel"),
  finish = list(title = "Finish drawing", text = "Finish"),
  undo = list(title = "Delete last point drawn", text = "Delete last point"),
  buttons = list(polyline = "Draw a polyline", polygon = "Draw a polygon", rectangle =
    "Draw a rectangle", circle = "Draw a circle", marker = "Draw a marker", circlemarker
    = "Draw a circlemarker")
)
```

Arguments

<code>actions</code>	List of options for actions toolbar button.
<code>finish</code>	List of options for finish toolbar button.
<code>undo</code>	List of options for undo toolbar button.
<code>buttons</code>	List of options for buttons toolbar button.

Examples

```
## Not run:  
library(leaflet)  
library(leaflet.extras)  
leaflet() %>%  
  addTiles() %>%  
  addDrawToolbar(  
    toolbar = toolbarOptions(  
      actions = list(text = "STOP"),  
      finish = list(text = "DONE"),  
      buttons = list(  
        polyline = "Draw a sexy polyline",  
        rectangle = "Draw a gigantic rectangle",  
        circlemarker = "Make a nice circle"  
      ),  
      ),  
      polylineOptions = T, rectangleOptions = T, circleOptions = T,  
      polygonOptions = F, markerOptions = F, circleMarkerOptions = F  
    )  
  
## End(Not run)
```

weatherIconList *Make weather-icon set*

Description

An icon can be represented as a list of the form `list(icon, markerColor, ...)`. This function is vectorized over its arguments to create a list of icon data. Shorter argument values will be re-cycled. `NULL` values for these arguments will be ignored.

Usage

```
weatherIconList(...)  
  
## S3 method for class 'leaflet_weather_icon_set'  
x[i]  
  
makeWeatherIcon(  
  icon,  
  markerColor = "red",  
  iconColor = "white",  
  extraClasses = NULL  
)  
  
weatherIcons(  
  icon,  
  markerColor = "red",
```

```

iconColor = "white",
extraClasses = NULL
)

addWeatherMarkers(
  map,
  lng = NULL,
  lat = NULL,
  layerId = NULL,
  group = NULL,
  icon = NULL,
  popup = NULL,
  popupOptions = NULL,
  label = NULL,
  labelOptions = NULL,
  options = leaflet::markerOptions(),
  clusterOptions = NULL,
  clusterId = NULL,
  data = leaflet::getMapData(map)
)

```

Arguments

...	icons created from <code>makeWeatherIcon()</code>
x	icons
i	offset
icon	the weather icon name w/o the "wi-" prefix. For a full list see https://erikflowers.github.io/weather-icons/
markerColor	color of the marker
iconColor	color of the weather icon
extraClasses	Character vector of extra classes.
map	a map widget object created from <code>leaflet()</code>
lng	a numeric vector of longitudes, or a one-sided formula of the form $\sim x$ where x is a variable in data; by default (if not explicitly provided), it will be automatically inferred from data by looking for a column named <code>lng</code> , <code>long</code> , or <code>longitude</code> (case-insensitively)
lat	a vector of latitudes or a formula (similar to the <code>lng</code> argument; the names <code>lat</code> and <code>latitude</code> are used when guessing the latitude column from <code>data</code>)
layerId	the layer id
group	the name of the group the newly created layers should belong to (for <code>clearGroup</code> and <code>addLayersControl</code> purposes). Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name.
popup	a character vector of the HTML content for the popups (you are recommended to escape the text using <code>htmlEscape()</code> for security reasons)

popupOptions	A Vector of <code>popupOptions</code> to provide popups
label	a character vector of the HTML content for the labels
labelOptions	A Vector of <code>labelOptions</code> to provide label options for each label. Default NULL
options	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
clusterOptions	if not NULL, markers will be clustered using <code>Leaflet.markercluster</code> ; you can use <code>markerClusterOptions()</code> to specify marker cluster options
clusterId	the id for the marker cluster layer
data	the data object from which the argument values are derived; by default, it is the data object provided to <code>leaflet()</code> initially, but can be overridden

Examples

```
iconSet <- weatherIconList(  
  hurricane = makeWeatherIcon(icon = "hurricane"),  
  tornado = makeWeatherIcon(icon = "tornado")  
)  
  
iconSet[c("hurricane", "tornado")]  
leaflet() %>%  
  addTiles() %>%  
  addWeatherMarkers(  
    lng = -118.456554, lat = 34.078039,  
    label = "This is a label",  
    icon = makeWeatherIcon(  
      icon = "hot",  
      iconColor = "#fffff77",  
      markerColor = "blue"  
    )  
  )  
  
## for more examples see  
# browseURL(system.file("examples/weatherIcons.R", package = "leaflet.extras"))
```

Index

* **GroupedLayersControl**
 addGroupedLayersControl, 18
 addGroupedOverlay, 19
 groupedLayersControlOptions, 45

* **datasets**
 leafletExtrasDependencies, 47
[.leaflet_pulse_icon_set
 (pulseIconList), 49
[.leaflet_weather_icon_set
 (weatherIconList), 55

activateGPS (gpsOptions), 44
addAwesomeMarkersDependencies, 2
addBingTiles, 3
addBootstrapDependency, 4
addBounceMarkers, 4
addControlGPS (gpsOptions), 44
addCSV (addGeoJSONv2), 9
addCSVHeatmap (addHeatmap), 20
addDrawToolbar, 6, 28, 38, 46, 54
addFullscreenControl, 8
addGeodesicPolylines (geodesics), 41
addGeoJSON, 9
addGeoJSONChoropleth (addGeoJSONv2), 9
addGeoJSONHeatmap (addHeatmap), 20
addGeoJSONv2, 9
addGPX (addGeoJSONv2), 9
addGPXHeatmap (addHeatmap), 20
addGreatCircles (geodesics), 41
addGroupedBaseLayer
 (addGroupedOverlay), 19
addGroupedLayersControl, 18, 20, 46
addGroupedOverlay, 18, 19, 46
addHash, 20
addHeatmap, 20
addKML (addGeoJSONv2), 9
addKMLChoropleth (addGeoJSONv2), 9
addKMLHeatmap (addHeatmap), 20
addLatLng (geodesics), 41
addLayersControl, 5, 13, 22, 30, 42, 50, 56

addMeasurePathToolbar
 (enableMeasurePath), 39
addPulseMarkers (pulseIconList), 49
addResetMapButton, 24
addReverseSearchGoogle (addSearchOSM),
 25
addReverseSearchOSM (addSearchOSM), 25
addSearchFeatures, 24
addSearchGoogle (addSearchOSM), 25
addSearchOSM, 25
addSearchUSCensusBureau (addSearchOSM),
 25
addStyleEditor, 27
addTiles, 40
addTopoJSON, 9
addWeatherMarkers (weatherIconList), 55
addWebGLCSVHeatmap (addWebGLHeatmap), 28
addWebGLGeoJSONHeatmap
 (addWebGLHeatmap), 28
addWebGLGPXHeatmap (addWebGLHeatmap), 28
addWebGLHeatmap, 28
addWebGLKMLHeatmap (addWebGLHeatmap), 28
addWMSLegend, 33

clearGroup, 5, 13, 22, 30, 42, 50, 56
clearHeatmap (addHeatmap), 20
clearSearchFeatures
 (addSearchFeatures), 24
clearSearchOSM (addSearchOSM), 25
clearWebGLHeatmap (addWebGLHeatmap), 28
colorNumeric, 23
csvParserOptions, 14, 23, 31
csvParserOptions (addGeoJSONv2), 9

deactivateGPS (gpsOptions), 44
debugMap, 34
drawCircleMarkerOptions, 7
drawCircleMarkerOptions
 (drawShapeOptions), 34
drawCircleOptions, 7

drawCircleOptions (drawShapeOptions), 34
drawMarkerOptions, 7
drawMarkerOptions (drawShapeOptions), 34
drawPolygonOptions, 6
drawPolygonOptions (drawShapeOptions),
 34
drawPolylineOptions, 6
drawPolylineOptions (drawShapeOptions),
 34
drawRectangleOptions, 7
drawRectangleOptions
 (drawShapeOptions), 34
drawShapeOptions, 34, 37

edithandlersOptions, 7, 38
editToolbarOptions, 7
editToolbarOptions (drawShapeOptions),
 34
edittoolbarOptions, 7, 38
enableMeasurePath, 39
enableTileCaching, 40

geodesics, 41
gpsOptions, 44
groupedLayersControlOptions, 18, 20, 45

handlersOptions, 7, 46
htmlEscape, 5, 43, 50, 56

iconList, 13
icons, 5, 43, 50

labelOptions, 5, 13, 43, 50, 57
leaflet, 5, 13, 22, 30, 33, 42, 50, 56
leafletExtrasDependencies, 47
legendOptions (addGeoJSONv2), 9

makeAwesomeIcon, 26, 37, 53
makeIcon, 13, 26, 37, 53
makePulseIcon, 50
makePulseIcon (pulseIconList), 49
makeWeatherIcon, 56
makeWeatherIcon (weatherIconList), 55
markerClusterOptions, 13, 50, 57
markerOptions, 43
measurePathOptions (enableMeasurePath),
 39

popupOptions, 5, 13, 43, 50, 57
propsToHTML, 48

propstoHTMLTable (propsToHTML), 48
pulseIconList, 49
pulseIcons (pulseIconList), 49

removeControlGPS (gpsOptions), 44
removeDrawToolbar (addDrawToolbar), 6
removeGroupedLayersControl
 (addGroupedOverlay), 19
removeGroupedOverlay
 (addGroupedOverlay), 19
removeHeatmap (addHeatmap), 20
removeSearchFeatures
 (addSearchFeatures), 24
removeSearchGoogle (addSearchOSM), 25
removeSearchOSM (addSearchOSM), 25
removeSearchUSCensusBureau
 (addSearchOSM), 25
removeStyleEditor (addStyleEditor), 27
removeWebGLHeatmap (addWebGLHeatmap), 28

searchFeaturesOptions (searchOptions),
 51
searchOptions, 51, 53
searchOSMText (addSearchOSM), 25
selectedPathOptions, 37
selectedPathOptions (drawShapeOptions),
 34
setMapWidgetStyle (propsToHTML), 48
suspendScroll, 53

tileOptions, 40
toolbarOptions, 7, 54

weatherIconList, 55
weatherIcons (weatherIconList), 55